## LISTING OF CLAIMS

1. (currently amended) An ad-hoc radio communication verification system, comprising:

means for sending data for verification data generation from one data send/receive device to the other send/receive device, wherein the two send/receive devices are mutually connected by an ad-hoc radio connection;

in the one data send/receive device, means for generating verification data from the sent data for verification data generation produced using based on a first generation algorithm and outputting the generated verification data to its own verification data output section:

in the other data send/receive device, means for generating verification data from the received data for verification data generation produced using based on the first generation algorithm and outputting the generated verification data to its own verification data output section; and

means for determining whether the verification data at the verification data output sections of both the data send/receive devices matches mutually\_ JP920000134US1 -3-

wherein the first generation algorithm generates a plurality of verification data, wherein for each verification data, it is determined whether the verification data at the verification data output sections of both the data send/receive devices match mutually.

- 2. (original) The ad-hoc radio communication verification system according to claim 1, wherein the verification data is visual or auditory verification data.
- 3. (original) The ad-hoc radio communication verification system according to claim 1, wherein the verification data is output at the verification data output section both in the visual form and auditory form.
- (currently amended) The ad-hoc radio communication verification system according to claim 1. further comprising:

means for defining a function as an operator, for defining a numeric on which the operator operates as an input to of the operator, and for defining an operation result of the operator as an output of the operator;

1

Serial No. 09/884,672 Art Unit No. 2134

means for establishing a serial sequence of operators that are composed of more than one or more of operators arranged in series, wherein the operators relate to the same or different one-way functions; and

means for letting an input to the serial sequence of operators be the data for verification data generation and an output from the serial sequence of operators or a corresponding value be the verification data.

### 5. (canceled)

(currently amended) The ad-hoc radio communication verification system according to <a href="claim 1">claim 5</a>, further comprising:

means for defining a function as an operator, for defining a numeric on which the operator operates as an input to of the operator, and for defining an operation result of the operator as an output of the operator;

means for establishing a serial sequence of operators that are composed of two or more of operators arranged in series, wherein the operators relate to the same different one-way functions;

p.7

## Serial No. 09/884,672 Art Unit No. 2134

means for letting an input to the serial sequence of operators be the data for verification data generation and outputs of two or more of operators selected from all operators composing the serial sequence of operators or corresponding values be the verification data respectively; and

means for determining for each verification data whether the verification data match mutually at the verification data output sections of both the data send/receive devices.

(currently amended) The ad-hoc radio communication verification system according to claim 1 claim 5, further comprising:

means for defining a function as an operator, for defining a numeric on which the operator operates as an input for of the operator, and for defining an operation result of the operator as an output of the operator;

means for establishing a plurality of operators that relate to mutually different one-way functions;

means for letting the data for verification data generation be a common input to each operator and an output

operator or a corresponding each value be the verification data respectively; and

means for determining for each verification data whether the verification data match mutually at verification data output sections of both the data send/receive devices.

- 8. (original) The ad-hoc radio communication verification system according to claim 1, wherein the data for verification data generation is a public key of either data send/receive device.
- 9. (currently amended) An ad-hoc radio communication data send/receive system utilizing the ad-hoc radio communication verification system according to claim 8, comprising:

for each user, a portable terminal having a radio communication function and a personal computer having a radio communication function that are owned by each user, wherein the portable terminal and personal computer of each user are connected by a secure communication path; and wherein each portable terminal comprises transmission means whereby when the ad hoc radio communication verification system verifies that a public key Kp of one user is

transmitted from the portable terminal of the one user to the portable terminal of the other user without being tampered with, as determined by the ad-hoc radio communication system, and the public key Kp is transmitted from the portable terminal to the personal computer of each user, and wherein each personal computer comprises means to generate a symmetric key Kc such that then the personal computer of the other user generates a symmetric key Kc produced using based on a second generation algorithm, while the personal computer of the one user generates the symmetric key Kc <u>produced using</u> based on the second generation algorithm from information including a random number and an identifier for the second generation algorithm transmitted from the personal computer of the other user in cipher using according to the public key; and thereafter both the personal computers send and receive data in cipher using according to the symmetric key Kc.

10. (currently amended) An ad-hoc radio communication data send/receive system utilizing the ad-hoc radio communication verification system according to claim 8, comprising, for each user, a portable terminal having a radio communication function and a personal computer having radio JP920000134US1 -8-

communication function that are owned by each user, wherein the portable terminal and personal computer of each user are connected by a secure communication path; when the ad-hoc radio communication verification system verifies that a public key Kp of one user is transmitted from the portable terminal of the one user to the portable terminal of the other user without being tampered with, and wherein each personal computer comprises means to generate a symmetric key Kc such that the portable terminal of the other user generates a symmetric key Kc <u>produced using</u> based on a second generation algorithm, while the portable terminal of the one user generates the symmetric key Kc produced using based on the second generation algorithm from information transmitted from the portable terminal of the other user in cipher according to the public key, then the symmetric key Kc is transmitted from the portable terminal to the personal computer of each user; and thereafter both the personal computers send and receive data in cipher using according to the symmetric key Kc.

11. (currently amended) An ad-hoc radio communication data send/receive system, comprising, for each user, a portable terminal having a radio communication function and a personal computer having a radio communication function that are owned by each user, wherein the portable terminal and personal computer of each user are connected by a secure communication path; when it is verified that a public key Kp of one user is transmitted from the portable terminal of the one user to the portable terminal of the other user without being tampered with, the public key Kp is transmitted from the portable terminal to the personal computer of each user, and wherein each personal computer comprises means to generate a symmetric key Kc such that then the personal computer of the other user generates a symmetric key Kc produced using based on a second generation algorithm, while the personal computer of the one user generates the symmetric key Kc produced using based on the second generation algorithm from information including a random number and an identifier for the second generation algorithm transmitted from the personal computer of the other user in cipher according to the public key; and thereafter both the

personal computers send and receive data in cipher <u>using</u> according to the symmetric key Kc.

12. (currently amended) An ad-hoc radio communication data send/receive system, comprising, for each user, a portable terminal having a radio communication function and a personal computer having a radio communication function that are owned by each user, wherein the portable terminal and personal computer of each user are connected by a secure communication path; when it is verified that a public key Kp of one user is transmitted from the portable terminal of the one user to the portable terminal of the other user without being tampered with, and wherein each personal computer comprises means to generate a symmetric key Kc such that the portable terminal of the other user generates a symmetric key Kc produced using based on a second generation algorithm, while the portable terminal of the one user generates the symmetric key Kc produced using based on the second generation algorithm from information transmitted from the portable terminal of the other user in cipher according to the public key, then the symmetric key Kc is transmitted from the portable terminal to the personal computer of each user; thereafter both the personal JP920000134US1 -11-

computers send and receive data in cipher using according to the symmetric key Kc.

(currently amended) A method for verifying an ad-hoc radio communication, comprising the steps of:

sending data for verification data generation from one data send/receive device to the other send/receive device, wherein the two send/receive devices are mutually connected by an ad-hoc radio connection;

in the one data send/receive device, generating verification data from the sent data for verification data generation produced using based on a first generation algorithm and outputting the generated verification data to its own verification data output section;

in the other data send/receive device, generating verification data from the received data for verification data generation produced using based on the first generation algorithm and outputting the generated verification data to its own verification data output section; and

determining whether the verification data at sections of both the data sections of both the data send/receive devices matches mutually,

wherein the first generation algorithm generates a plurality of verification data, wherein for each verification data, it is determined whether the verification data at the verification data output sections of both the data send/receive devices match mutually.

- 14. (original) The method according to claim 13, wherein the verification data is visual or auditory verification data.
- 15. (original) The method according to claim 13, wherein the verification data is output at the verification data output section both in the visual form and auditory form.
- 16. (currently amended) The method according to claim 13, further comprising the steps of:

defining a function as an operator, defining a numeric on which the operator operates as an input to hinspace ef the operator, and <u>defining</u> an operation result of the operator as an output of the operator;

establishing a serial sequence of operators that are composed of more than one or more of operators arranged in series, wherein the operators relate to the same or different one-way functions;

JP920000134US1

letting an input to the serial sequence of operators be the data for verification data generation and an output from the serial sequence of operators or a corresponding value be the verification data.

### 17. (canceled)

18. (currently amended) The method according to claim 13 claim 17, further comprising the steps of:

defining a function as an operator, defining a numeric on which the operator operates as an input to of the operator and defining an operation result of the operator as an output of the operator;

establishing a serial sequence of operators that are composed of two or more of operators arranged in series wherein the operators relate to the same or different one-way functions;

letting an input to the serial sequence of operators be the data for verification data generation and outputs of two or more of operators selected from all operators composing the serial sequence of operators or corresponding values be the verification data respectively; and

determining for each verification data whether the JP920000134US1 -14-

verification data match mutually at the verification data output sections of both the data send/receive devices.

19. (currently amended) The method according to claim 13 claim 17, further comprising the steps of:

defining a function as an operator, defining a numeric on which the operator operates as an input to of the operator, and <u>defining</u> an operation result of the operator as an output of the operator;

establishing a plurality of operators that relate to mutually different one-way functions;

letting the data for verification data generation be a common input to each operator and an output of each operator or a corresponding value be the verification data respectively; and

determining for each verification data whether the verification data match mutually at the verification data output sections of both the data send/receive devices.

(original) The method according to claim 13, wherein 20. the data for verification data generation is a public key of either data send/receive device.

21. (currently amended) The method for sending and receiving ad-hoc radio communication data, utilizing the verification method according to claim 20, comprising: a portable terminal having a radio communication function for each user and a personal computer having a radio communication function for that are owned by each user, wherein the portable terminal and personal computer of each user are connected by a secure communication path; when verification method verifies that a public key Kp of one user is transmitted from the portable terminal of the one user to the portable terminal of the other user without being tampered with, the public key Kp is transmitted from the portable terminal to the personal computer of each user, then the personal computer of the other user generates a symmetric key Kc produced using based on a second generation algorithm, while the personal computer of the one user generates the symmetric key Kc produced using based on the second generation algorithm from information including a random number and an identifier for the second generation algorithm transmitted from the personal computer of the other user in cipher according to the public key; and thereafter both the personal computers send and receive data in cipher using according to the symmetric key Kc.

JP920000134US1

22. (currently amended) The method for sending and-receiving ad-hoc radio communication data, utilizing the verification method according to claim 20, comprising: a portable terminal having a radio communication function for each user and a personal computer having a radio communication function for that are owned by each user, wherein the portable terminal and personal computer of each user are connected by a secure communication path; when the verification method verifies that a public key Kp of one user is transmitted from the portable terminal of the one user to the portable terminal of the other user without being tampered with, the portable terminal of the other user generates a symmetric key Kc <u>produced using</u> based on a second generation algorithm, while the portable terminal of the one user generates the symmetric key Kc produced using based on the second generation algorithm from information transmitted from the portable terminal of the other user in cipher according to the public key, then the symmetric key Kc is transmitted from the portable terminal to the personal computer of each user; and thereafter both the personal computers send and receive data in cipher using according to the symmetric key Kc.

JP920000134US1

23. (currently amended) The method for sending and receiving ad-hoc radio communication data, comprising: a portable terminal having a radio communication function for each user and a personal computer having a radio communication function for that are owned by each user, wherein the portable terminal and personal computer of each user are connected by a secure communication path; when it is verified that a public key Kp of one user is transmitted from the portable terminal of the one user to the portable terminal of the other user without being tampered with, the public key Kp is transmitted from the portable terminal to the personal computer of each user, then the personal computer of the other user generates a symmetric key Kc produced using based on a second generation algorithm, while the personal computer of the one user generates the symmetric key Kc <u>produced using</u> <del>based on</del> the second generation algorithm from information including a random number and an identifier for the second generation algorithm transmitted from the personal computer of the other user in cipher according to the public key; and thereafter both the personal computers send and receive data, in cipher using according to the symmetric key Kc.

24. (currently amended) The method for sending and receiving ad-hoc radio communication data, comprising: a portable terminal having a radio communication function for each user and a personal computer having a radio communication function for that are owned by each user, wherein the portable terminal and personal computer of each user are connected by a secure communication path; when it is verified that a public key Kp of one user is transmitted from the portable terminal of the one user to the portable terminal of the other user without being tampered with, the portable terminal of the other user generates a symmetric key Kc produced using based on a second generation algorithm, while the portable terminal of the one user generates the symmetric key Kc produced using based on the second generation algorithm from information transmitted from the portable terminal of the other user in cipher according to the public key, then the symmetric key Kc is transmitted from the portable terminal to the personal computer of each user; thereafter both the personal computers send and receive data in cipher using according to the symmetric key Kc.

25. (currently amended) A recording medium recording a program for an ad-hoc radio communication verification system, wherein the verification system comprising:

means for sending data for verification data generation from one data send/receive device to the other send/receive device, wherein the two send/receive devices are mutually connected by an ad-hoc radio connection;

in the one data send/receive device, means for generating verification data from the sent data for verification data generation produced using based on a first generation algorithm and outputting the generated verification data to its own verification data output section:

in the other data send/receive device, means for generating verification data from the received data for verification data generation produced using based on the first generation algorithm and outputting the generated verification data to its own verification data output section; and

means for determining whether the verification data at the verification data output sections of both the data send/receive devices matches mutually,

wherein the first generation algorithm generates a plurality of verification data, wherein for each verification data, it is determined whether the verification data at the verification data output sections of both the data send/receive devices match mutually.

- 26. (original) The recording medium according to claim 25, wherein the verification data is visual or auditory verification data.
- 27. (original) The recording medium according to claim 25, wherein the verification data is output at the verification data output section both in the visual form and auditory form.
- 28. (currently amended) The recording medium according to claim 25, wherein the verification system further comprising:

means for defining a function as an operator, for defining a numeric on which the operator operates as an input to of the operator, and for defining an operation result of the operator as an output of the operator;

p.23

Serial No. 09/884,672 Art Unit No. 2134

means for establishing a serial sequence of operators that are composed of more than one or more of operators arranged in series, wherein the operators relate to the same or different one-way functions; and

means for letting an input to the serial sequence of operators be the data for verification data generation and an output from the serial sequence of operators or a corresponding value be the verification data.

# 29. (canceled)

30. (currently amended) A delivery system for delivering a program for an ad-hoc radio communication system, the verification system comprising:

means for sending data for verification data generation from one data send/receive device to the other send/receive device, wherein the two send/receive devices are mutually connected by an ad-hoc radio connection;

in the one data send/receive device, means for generating verification data from the for data verification data generation produced using based on a first generated the outputting generation algorithm and

-22-

p.24

Serial No. 09/884,672 Art Unit No. 2134

verification data to its own verification data output section;

in the other data send/receive device, means for generating verification data from the received data for verification data generation produced using based on the first generation algorithm and outputting the generated verification data to its own verification data output section; and

means for determining whether the verification data at the verification data output sections of both the data send/receive devices matches mutually\_

wherein the first generation algorithm generates a plurality of verification data, wherein for each verification data, it is determined whether the verification data at the verification data output sections of both the data send/receive devices match mutually.

31. (currently amended) A computer program comprising a computer usable medium having computer readable program code means embodied therein for causing ad-hoc radio communication, the computer readable program code means in said computer program product comprising computer readable

program code means for causing a computer to effect the functions of claim 1.

- 32. (currently amended) 31. A computer program product comprising a computer usable medium having computer readable program code means embodied therein for causing ad-hoc radio communication, the computer readable program code means in said computer program product comprising computer readable program code means for causing a computer to effect the functions of claim 4 +.
- (currently amended) A computer program product 33. comprising a computer usable medium having computer readable program code means embodied therein for causing ad-hoc radio communication, the computer readable program code means in said computer program product comprising computer readable program code means for causing a computer to effect the the functions of claim 9.
- (currently amended) A computer program product 34. comprising a computer usable medium having computer readable program code means embodied therein for causing ad-hoc radio communication, the computer readable program code means in -24-JP920000134US1

p.26

Serial No. 09/884,672 Art Unit No. 2134

said computer program product comprising computer readable program code means for causing a computer to effect the the functions of claim 10.

35. (original) A computer program product comprising a computer usable medium having computer readable program code means embodied therein for causing ad-hoc radio communication, the computer readable program code means in said computer program product comprising computer readable program code means for causing a computer to effect the functions of claim 11.

## 36. (canceled)

37. (original) An article of manufacture comprising a computer usable medium having computer readable program code means embodied therein for causing ad-hoc radio communication, the computer readable program code means in said article of manufacture comprising computer readable program code means for causing a computer to effect the steps of claim 13.

- 38. (original) An article of manufacture comprising a computer usable medium having computer readable program code means embodied therein for causing ad-hoc radio communication, the computer readable program code means in said article of manufacture comprising computer readable program code means for causing a computer to effect the steps of claim 21.
- 39. (original) An article of manufacture comprising a computer usable medium having computer readable program code means embodied therein for causing ad-hoc radio communication, the computer readable program code means in said article of manufacture comprising computer readable program code means for causing a computer to effect the steps of claim 22.
- 40. (original) An article of manufacture comprising a computer usable medium having computer readable program code means embodied therein for causing ad-hoc radio communication, the computer readable program code means in said article of manufacture comprising computer readable program code means for causing a computer to effect the steps of claim 23.

JP920000134US1

- 41. (original) An article of manufacture comprising a computer usable medium having computer readable program code ad-hoc radio causing therein for embodied means communication, the computer readable program code means in said article of manufacture comprising computer readable program code means for causing a computer to effect the steps of claim 24.
- 42. (canceled)
- 43. (canceled)